

MODEL	POWER	ACTION	LENGTH	CLOSED LENGTH	SECTION	WEIGHT	TIPTOP	BUTEND	LURE WT oz	LURE WT g	LINE LB	LINE kg	CARBON %	GLASS %
701MFB	M	F	2.14(7'0")	214	1	120	1.8	12.4	1/4-3/4	7-21	10-17	5-8	89	11
701MHFB	MH	F	2.14(7'0")	214	1	123	2	12.4	1/4-1	7-28	10-20	5-9	87	13
731HFB	H	F	2.21(7'3")	221	1	168	2	13.4	3/8-1 1/2	11-42	12-25	6-12	92	8
701MLFS	ML	F	2.13(7'0")	213	1	110	1.6	11.4	1/8-3/8	3.5-11	6-12	2-6	88	12
701MFS	M	F	2.13(7'0")	213	1	114	1.9	11.4	1/8-3/4	3.5-21	6-14	2-7	87	13
701MHFS	MH	F	2.13(7'0")	213	1	117	1.9	12.4	1/4-3/4	7-21	8-17	4-8	89	11
702MFS	M	F	2.13(7'0")	111	2	114	1.7	11.4	1/8-3/4	3.5-21	6-14	2-7	93	7
601HFB	H	F	1.83(6'0")	183	1	124	2	11.4	3/8-1 1/2	11-42	13-26	6-12	92	8
701HFS	H	F	2.13(7'0")	213	1	137	1.6	11.4	1/8-1	3.5-28	13-26	6-12	93	7
702ULXS	UL	XF	2.13(7'0")	111	2	95	1.3	10.4	1/64-1/8	0.45-3.5	2-4	1-2	92	8
702LXS	L	XF	2.13(7'0")	111	2	115	1.5	11.4	1/32-1/4	0.9-7	3-6	1.5-3	93	7
762MHFS	MH	F	2.29(7'6")	119	2	141	1.6	12.4	1/8-3/4	3.5-21	11-19	5-9	94	6
762XHFS	XH	F	2.29(7'6")	119	2	151	1.9	13.4	1/2-1 1/2	14-42	15-33	7-15	93	7