

MODEL	POWER	ACTION	LENGTH	CLOSED LENGTH	SECTION	WEIGHT	TIPTOP	BUTEND	LURE WT oz	LURE WT g	LINE LB	LINE kg	CARBON %	GLASS %
702MFS	M	F	2.13(7'0")	111	2	114	1.7	11.4	1/8-3/4	3.5-21	6-14	2-7	93	7
762MHFS	MH	F	2.29(7'6")	119	2	141	1.6	12.4	1/8-3/4	3.5-21	11-19	5-9	94	6
662MLRB	ML	R	1.98(6'6")	103	2	105	1.6	10.4	1/8-1/2	3.5-14	6-14		91	9
6102MRB	M	R	2.08(6'10")	108	2	118	1.8	11.4	3/16-3/4	5-21	8-16		92	8
732HFB	H	F	2.21(7'3")	115	2	135	2	13.4	3/8-1 1/2	11-42	12-25		92	8
662MRB-G	M	R	1.98(6'6")	103	2	118	2	12.4	3/16-3/4	5-21	8-16		60	40
642ULXS-ST	UL	XF	1.93(6'4")	100	2	80	0.8	9.4	1/64-1/8	0.45-3.5	1.5-4		92	8
642LFS	L	F	1.93(6'4")	100	2	87	1.4	9.4	1/32-1/4	0.9-7	2.5-6		91	9
682MLFS	ML	F	2.03(6'8")	105	2	93	1.4	10.4	1/16-3/8	1.8-11	4-8		92	8