

MODEL	POWER	ACTION	LENGTH	CLOSED LENGTH	SECTION	WEIGHT	TIPTOP	BUTEND	LURE WT oz	LURE WT g	LINE LB	LINE PE(#)	CARBON %	GLASS %
652LFB	L	F	1.96(6'5")	102	2	100	1.5	9.4	1/16-3/8	1.8-11	5-12		91	9
662MLRB	ML	R	1.98(6'6")	103	2	105	1.6	10.4	1/8-1/2	3.5-14	6-14		91	9
662MFB	M	D	1.98(6'6")	103	2	113	1.8	11.4	3/16-3/4	5-21	8-16		92	8
672MHFB	MH	D	2.01(6'7")	105	2	120	1.9	12.4	1/4-1	7-28	10-20	MAX#5	93	7
6102MRB	M	R	2.08(6'10")	108	2	118	1.8	11.4	3/16-3/4	5-21	8-16		92	8
6102MHRB	MH	R	2.08(6'10")	108	2	126	2	12.4	1/4-1	7-28	10-20		92	8
6102HFB	H	F	2.08(6'10")	108	2	129	2	13.4	3/8-1 1/2	11-42	12-25		92	8
6112HSB	H	S	2.11(6'11")	110	2	133	1.8	13.4	3/8-4	11-113	14-30	MAX#5	93	7
732MHFB	MH	F	2.21(7'3")	115	2	131	2	12.4	1/4-1	7-28	10-20		93	7
732HFB	H	F	2.21(7'3")	115	2	135	2	13.4	3/8-1 1/2	11-42	12-25		92	8
662MRB-G	M	R	1.98(6'6")	103	2	118	2	12.4	3/16-3/4	5-21	8-16		60	40
622ULXS	UL	XF	1.88(6'2")	98	2	80	1.3	9.4	1/64-1/8	0.45-3.5	1.5-4		87	13
642ULXS-ST	UL	XF	1.93(6'4")	100	2	80	0.8	9.4	1/64-1/8	0.45-3.5	1.5-4		92	8
642LFS	L	F	1.93(6'4")	100	2	87	1.4	9.4	1/32-1/4	0.9-7	2.5-6		91	9
682LFS	L	F	2.03(6'8")	105	2	89	1.4	9.4	1/32-1/4	0.9-7	2.5-6		92	8
682MLFS	ML	F	2.03(6'8")	105	2	93	1.4	10.4	1/16-3/8	1.8-11	4-8		92	8
682MHRS	MH	R	2.03(6'8")	105	2	117	2	12.4	1/8-3/4	3.5-21	8-20	0.8-2.0	90	10