

| MODEL | POWER | ACTION | LENGTH | CLOSED LENGTH | SECTION | WEIGHT | TIPTOP | BUTEND | LURE WT oz | LURE WT g | LINE LB | LINE kg | LINE PE(#) | CARBON % | GLASS % |
|------------|-------|--------|-------------|------------------|---------|--------|--------|--------|---------------|--------------|------------|------------|---------------|-------------|------------|
| 702MFS | M | F | 2.13(7'0") | 111 | 2 | 114 | 1.7 | 11.4 | 1/8-3/4 | 3.5-21 | 6-14 | 2-7 | | 93 | 7 |
| 601HFB | H | F | 1.83(6'0") | 183 | 1 | 124 | 2 | 11.4 | 3/8-1 1/2 | 11-42 | 13-26 | 6-12 | | 92 | 8 |
| 762MHFS | MH | F | 2.29(7'6") | 119 | 2 | 141 | 1.6 | 12.4 | 1/8-3/4 | 3.5-21 | 11-19 | 5-9 | | 94 | 6 |
| 762XHFS | XH | F | 2.29(7'6") | 119 | 2 | 151 | 1.9 | 13.4 | 1/2-1 1/2 | 14-42 | 15-33 | 7-15 | | 93 | 7 |
| 662MLRB | ML | R | 1.98(6'6") | 103 | 2 | 105 | 1.6 | 10.4 | 1/8-1/2 | 3.5-14 | 6-14 | | | 91 | 9 |
| 672MHFB | MH | D | 2.01(6'7") | 105 | 2 | 120 | 1.9 | 12.4 | 1/4-1 | 7-28 | 10-20 | | MAX#5 | 93 | 7 |
| 6102MRB | M | R | 2.08(6'10") | 108 | 2 | 118 | 1.8 | 11.4 | 3/16-3/4 | 5-21 | 8-16 | | | 92 | 8 |
| 662MRB-G | M | R | 1.98(6'6") | 103 | 2 | 118 | 2 | 12.4 | 3/16-3/4 | 5-21 | 8-16 | | | 60 | 40 |
| 642ULXS-ST | UL | XF | 1.93(6'4") | 100 | 2 | 80 | 0.8 | 9.4 | 1/64-1/8 | 0.45-3.5 | 1.5-4 | | | 92 | 8 |
| 682MHRS | MH | R | 2.03(6'8") | 105 | 2 | 117 | 2 | 12.4 | 1/8-3/4 | 3.5-21 | 8-20 | | 0.8-2.0 | 90 | 10 |