

| MODEL      | POWER | ACTION | LENGTH      | CLOSED LENGTH | SECTION | WEIGHT | TIPTOP | BUTEND | LURE WT oz | LURE WT g | LINE LB | LINE PE(#) | CARBON % | GLASS % |
|------------|-------|--------|-------------|---------------|---------|--------|--------|--------|------------|-----------|---------|------------|----------|---------|
| 652LFB     | L     | F      | 1.96(6'5")  | 102           | 2       | 100    | 1.5    | 9.4    | 1/16-3/8   | 1.8-11    | 5-12    |            | 91       | 9       |
| 662MLRB    | ML    | R      | 1.98(6'6")  | 103           | 2       | 105    | 1.6    | 10.4   | 1/8-1/2    | 3.5-14    | 6-14    |            | 91       | 9       |
| 6102MRB    | M     | R      | 2.08(6'10") | 108           | 2       | 118    | 1.8    | 11.4   | 3/16-3/4   | 5-21      | 8-16    |            | 92       | 8       |
| 6102MHRB   | MH    | R      | 2.08(6'10") | 108           | 2       | 126    | 2      | 12.4   | 1/4-1      | 7-28      | 10-20   |            | 92       | 8       |
| 6102HFB    | H     | F      | 2.08(6'10") | 108           | 2       | 129    | 2      | 13.4   | 3/8-1 1/2  | 11-42     | 12-25   |            | 92       | 8       |
| 732MHFB    | MH    | F      | 2.21(7'3")  | 115           | 2       | 131    | 2      | 12.4   | 1/4-1      | 7-28      | 10-20   |            | 93       | 7       |
| 622ULXS    | UL    | XF     | 1.88(6'2")  | 98            | 2       | 80     | 1.3    | 9.4    | 1/64-1/8   | 0.45-3.5  | 1.5-4   |            | 87       | 13      |
| 642ULXS-ST | UL    | XF     | 1.93(6'4")  | 100           | 2       | 80     | 0.8    | 9.4    | 1/64-1/8   | 0.45-3.5  | 1.5-4   |            | 92       | 8       |
| 642LFS     | L     | F      | 1.93(6'4")  | 100           | 2       | 87     | 1.4    | 9.4    | 1/32-1/4   | 0.9-7     | 2.5-6   |            | 91       | 9       |
| 682LFS     | L     | F      | 2.03(6'8")  | 105           | 2       | 89     | 1.4    | 9.4    | 1/32-1/4   | 0.9-7     | 2.5-6   |            | 92       | 8       |
| 682MLFS    | ML    | F      | 2.03(6'8")  | 105           | 2       | 93     | 1.4    | 10.4   | 1/16-3/8   | 1.8-11    | 4-8     |            | 92       | 8       |
| 682MHRS    | MH    | R      | 2.03(6'8")  | 105           | 2       | 117    | 2      | 12.4   | 1/8-3/4    | 3.5-21    | 8-20    | 0.8-2.0    | 90       | 10      |